

Deluxe 3-Temp Water Dispenser

Bottle-less water dispenser with filtration provides more hot, room and cold temperature water from your tap that is safe, clean and great tasting.

Features

- Three temperature system: Hot, Room and Cold
- Separate hot /cold power switches on rear panel
- Easy to use microprocessor control panel on front
 Separate hot/cold power switched
 Reboil raises water 15° F over normal hot water temperature
 Automatic heating control with over-temperature shut-off
- Built-in filtration system is front panel accessible for easy replacement
 Available with Reverse Osmosis filtration system
 Or Standard Dual-Cartridge filtration system
- Sealed compressor cooling system with adjustable thermostat, 37-50° F
- Mechanical float valve shut-off
- Type 304 stainless steel hot and cold water tanks
- Built-In water level indicator
- Safety lock for hot water faucet
- Available with ultraviolet or ozone sterilizer
- 1 year limited warranty 3 year compressor warranty



Filter assembly is front panel accessible

Executive Gray option



Specifications

Weight: 60 lb. Dimension: 16"W x 13"D x 41"H

Floor to spigot: 29"
Spigot to Drip Tray: 7"
Cold tank volume .5 gal

Hot tank volume .5 gal Room tank volume 2.2 gal Cooling Rate: 1.5 gal/hr 37-50 °F

Heating Rate: 1.5 gal/hr 180 °F

Voltage: 115 VAC Power Required: 600w max

Filter System

Standard Filter 2000F

Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Reverse Osmosis Filter 2000R

Above 2 stages plus

Stage 3: 50-GPD RO Membrane

Automatic tank full control Fully assembled

- connection hardware included

Meets Energy Star Requirements ADA compliant

ORDERING INFORMATION

3-Temp Model - 50 GPD Reverse Osmosis **PWC-2000R** 3-Temp Model - Standard Filtration **PWC-2000F Executive Gray Cabinet** add /EG add /UV 3-temp Model with UV sterilizer 3-temp Model with Ozone sanitizer add /OZ 2-temp Model w/ ProTekk Leak Detector add /ldm Cup holder call factory **Replacement Filters** Sediment IFA-4035

GAC Carbon IFA-4034 RO membrane, 50 GPD MA-4203





